

Jamo D 600



The D 600 SUB is built around a very powerful 380mm / 15inch low frequency driver, controlled by our Motional Feedback (MFB) and equipped with a solid 400W (continuous output) class-D amplifier capable of delivering peak power in excess of 1600W.

The standby power consumption is less than 1W. To make it easy to place the D 600 SUB in the room it is equipped with adjustable Boundary Gain Compensation. The Boundary Gain can be adjusted in steps, and adjusts in the region between 55Hz and 20Hz with as much as -10dB at 20Hz.

All controls on the D 600 SUB are placed in the top of the cabinet which allows for easily accessibility. All functions are controlled by a dedicated digital processor that ensures maximum precision and repeatability.

Jamo has developed state-of-the-art technology driver units specifically for this high-end THX Ultra 2 system. Identical drivers used in both the LCR and surround-speakers result in perfect balance, and a 15"/1600W subwoofer equipped with Motional Feedback ensures dynamic, detailed and precise reproduction of even the lowest spectrum. The subwoofer is equipped with a unique touch interface, giving the user a variety of settings.

Specifications

System	Active DSP based subwoofer, sealed enclosure, Motional Feedback
User interface	Touch panel with backlight
Woofer (mm / in)	380 / 15
Rated power (Wrms)	600 @4ΩTHD+N <1%
Dynamic power (Wrms)	800 @4Ω
Peak power (Wpk)	1600 @4Ω
Maximum SPL (dB)	109
Frequency range (Hz)	20 - 200
Variable cut off (Hz)	40 - 200
Phase (deg.)	0 to -180
BGC	Variable
Line input	Yes, stereo pass through for daisy chain
LFE input	Yes, pass through for daisy chain
Sensitivity (mVrms)	100
Sound modes	Default, personal, THX
12V trigger	Yes, pass through for daisy chain
Mains switch	On / Off
Voltage switch (fuse)	115V/60Hz (6.3A) / 230V/50Hz (3.15 A)
Auto enable switch	Off / Auto / On
Dimension (mm / in)	557 x 587 x 501 / 21.9 x 23.1 x 19.7
Weight (kg / lb)	32 / 70.5
Finish	Stone Grey



D 600 SUB with grille



D 600 SUB without grille



Jamo[®]
Danish Sound Design

jamo.com

One D 600 SUB will meet THX Select2 output levels.

THX and the THX logo are trademarks of THX Ltd.

which may be registered in some jurisdictions. All rights reserved.

© 2012 Klipsch Group, Inc. A wholly-owned subsidiary of VOXX International Corporation